

## **PF 2001B** **DUCT LINER SPRAY ADHESIVE**

*PF 2001B SOLVENT BASED/NON-FLAMMABLE ADHESIVE is designed to bond low density fiberglass insulation to interior and exterior of sheet metal air conditioning ducts. It is also an excellent adhesive used to bond urethane foam, felt and cork to metal, wood and plastic surfaces. PF 2001B offers fast tacking and excellent sprayability without cob webbing or clogging of equipment.*

**COLORS:** Blue

**ODOR:** Mild when wet; none when dry.

**BASE:** Methylene Chloride

**VOLATILE MATERIAL:** Aliphatic hydrocarbons

**DENSITY:** 10.2 ± 0.5 lbs./gal

**SOLIDS CONTENT:** 13.5% ± 2%.

**COVERAGE:** 450 - 600 sq. ft./gal.

**APPLICATION TEMPERATURE RANGE:** 30°F to 110°F.

**SERVICE TEMPERATURE RANGE:** -20°F to 200°F.

**BONDING RANGE:** Immediate to 5 minutes

**STORAGE:** Store between 60°F and 90°F.

**SHELF LIFE:** One year in unopened container.

**CLEANUP:** Mineral spirits

**ASTM C-916:** Meets type IV criteria for insulation adhesives.

**PHYSICAL AND CHEMICAL RESISTANCE:** Excellent resistance to moisture and aging.

**PRECAUTIONS:** Avoid prolonged breathing of vapors or repeated skin contact. Keep closed when not in use.

**APPLICATION SUGGESTIONS:** Spray, brush or roll

**NOTICE TO PURCHASER:** Please see the product label for important limited warranty information.

Revision date 03/03

**ITW TACC**

56 Air Station Industrial Park  
Rockland, MA 02370

TOLL FREE 1-800-503-6991 FAX 1-800-231-8222  
www.itwtacc.com info@itwtacc.com