

UNIT SIZE	MAX L/S	MAX CFM	S.I. UNITS mm				IMPERIAL UNITS inches			
			OUTLET		INLET	LENGTH	OUTLET		INLET	LENGTH
			B	C	A	L	B	C	A	L
4	106	225	305	203	102	562	12	8	4	22 1/8
5	165	350			127				5	
6	212	450			152				6	
7	307	650	305	254	178	511	12	10	7	20 1/8
8	378	800			203				8	
9	496	1050			229				9	
10	637	1350	356	318	254		14	12 1/2	10	
12	991	2100			305				12	
14	1416	3000	508	445	356	600	20	17 1/2	14	23 5/8
16	1888	4000	610	457	406				24	

**NOTES:**

- INTERNAL INSULATION 1/2" (13mm) DUAL DENSITY WHICH MEETS REQUIREMENTS OF NFPA 90A AND UL181.
- 22GA. ZINC COATED STEEL HOUSING. MECHANICALLY SEALED AND GASKETED, LEAK RESISTANT CONSTRUCTION.
- RECTANGULAR DISCHARGE OPENING WITH SLIP AND DRIVE CLEAT DUCT CONNECTION.
- DIGITAL CONTROLS BY CONTROL CONTRACTOR.

**SDV5000 INCLUDES:**


- MULTI-POINT SENSOR c/w GAUGE TAPS SUPPLIED BY PRICE.

**OPTIONS:**

- CONTROLS ENCLOSURE
- DISCONNECT SWITCH

LINERS AND CONSTRUCTION OPTIONS:  
(REFER TO ATTACHED SUBMITTAL)

- FF       PM       SM       AF
- WF       WFPM       AFPM       LL
- LTAF\*       LTFF\*
- CRAF       CRWF



ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

<b>PROJECT:</b>		<b>PRICE</b> <sup>®</sup>	
<b>ENGINEER:</b>		<b>BG</b>	<b>SDV5000</b> SINGLE DUCT TERMINAL VARIABLE VOLUME DIGITAL CONTROL
<b>CUSTOMER:</b>		219476	
<b>SUBMITTAL DATE:</b>	<b>SPEC. SYMBOL:</b>	SEPT. 2002	